


Surge-Trap® K - K2 PV

Photovoltaic & Energy Storage SPDs
DIN RAIL - IEC TYPE 2 PV



General Data

Internal configuration	+, -, PE
No. Poles	3-Pole
No. DIN rail modules	3
Network configuration	YPV
IEC SPD Type	Class II
EN SPD Type	PV Type2
UL SPD Type	Type 1 Component Assembly
Format	Pluggable
Protection Modes	L+/PE, L-/PE, L+/L-
Product standards	IEC/EN 61643-31; UL 1449 5th Edition



PART NUMBERS

XXXX	1000	1500
K2-PVXXXX	44020312	44020316
K2-PVXXXX-M (with Microswitch)	44020313	44020317

SURGE PROTECTION DEVICE (SPD) - IEC TECHNICAL FEATURES

K2-PVXXXX, K2-PVXXXX-M (with Microswitch)	1000	1500
Maximum continuous operating voltage (DC) - Ucpv [V]	1170	1500
Nominal discharge current (8/20)- In [kA]		20
Max Discharge Current (8/20) - Imax [kA]		50
Voltage protection level at In - Up [kV]	≤3,75	≤4,75
Voltage protection level at In - Up (L-PE) [kV]	≤3,75	≤4,75
Short Circuit Withstand- Iscpv [kA]		20
Total discharge current (8/20) - Itotal [kA]		50
Response time - tA [ns]		≤25
Dynamic thermal disconnection		Yes
No. of ports		1

SURGE PROTECTION DEVICE (SPD) - UL TECHNICAL FEATURES

K2-PVXXXX, K2-PVXXXX-M (with Microswitch)	1000	1500
Nominal discharge current (8/20) - In [kA]		20
Maximum continuous operating voltage - MCOV (DC+ DC-) [V]	1170	1500
Maximum continuous operating voltage - MCOV (DC+ G) [V]	1170	1500
Voltage protection rating - VPR (DC- G) [V]	3000	4000
Voltage protection rating - VPR (DC+ DC-) [V]	3000	4000
Voltage protection rating - VPR (DC+ G) [V]	3000	4000
Short-Circuit Current Rating-SCCR [kA]	50	65

DATASHEET


This document is subject to change at any time without notice www.mersen.com | Lepanto 49 · 08223 Terrassa, Barcelona Spain © 2025 Cirprotec SLU | All rights reserved




Surge-Trap® K - K2 PV

Photovoltaic & Energy Storage SPDs
DIN RAIL - IEC TYPE 2 PV

MECHANICAL AND ENVIRONMENTAL FEATURES		
K2-PVXXXX, K2-PVXXXX-M (with Microswitch)	1000	1500
Temperature range [°C]	-40 ... 85	
Humidity range [%]	5 ... 95	
Max. Altitude [m]	2000	
Indication System Type	Green (OK) / Not green (replace)	
Insulating material	PA6 CT1 & PA66 CT1	
Housing color	Grey RAL 7035	
Enclosure - IP	IP20	
Flammability class	UL94 V-0	
Solid conductor cross section	1,5...35 mm²	
Stranded conductor cross section	1,5...25 mm²	
Torque rating [N m]	3	
Remote indication conductor cross section [mm²]	0.5 ... 1.5	
Remote indication switching capacity [V/A]	AC: 250/0.5 DC: 30/1	
Remote Indication Torque [N m]	3	

DIMENSIONS AND WEIGHT		
	K2-PVXXXX K2-PVXXXX-M (with Microswitch)	10001500
	Net Weight [kg]	0.3220.348
	Gross weight [kg]	0.3420.369
	Packaging dimensions (H x W x L) [mm]	118 × 59 × 97

INTERNAL CONFIGURATION		
	REPLACEMENT CARTRIDGES	
	K2-PVXXXX K2-PVXXXX-M (with Microswitch)	10001500
	K2-XXXX	4402000744020009